


415CO
Punte elicoidali cilindriche serie corta, in acciaio HSS-CO 5% rettificate
DIN 338 ISO 235
 $R \leq 1200 \text{ N/mm}^2$
 $HV \sim 800 \div 860$

	art.	L1 mm	L mm	Ø mm
004150310	415CO 1,0	12	34	1,00
004150312	415CO 1,50	18	40	1,50
004150314	415CO 2,00	24	49	2,00
004150316	415CO 2,50	30	57	2,50
004150320	415CO 3,00	33	61	3,00
004150322	415CO 3,50	39	70	3,50
004150324	415CO 4,00	43	75	4,00
004150326	415CO 4,50	47	80	4,50
004150328	415CO 5,00	52	86	5,00
004150330	415CO 5,50	57	93	5,50
004150332	415CO 6,00	57	93	6,00
004150334	415CO 6,50	63	101	6,50
004150336	415CO 7,00	69	109	7,00
004150338	415CO 7,50	69	109	7,50
004150340	415CO 8,00	75	117	8,00
004150342	415CO 8,50	75	117	8,50
004150344	415CO 9,00	81	125	9,00
004150346	415CO 9,50	81	125	9,50
004150348	415CO 10,00	87	133	10,00
004150350	415CO 10,50	87	133	10,50
004150352	415CO 11,00	94	142	11,00
004150354	415CO 11,50	94	142	11,50
004150356	415CO 12,00	101	151	12,00
004150358	415CO 12,50	101	151	12,50
004150360	415CO 13,00	101	151	13,00

